

SERIES AVD IP

IP FRONT DOOR STATION VIDEO

SURFACE-MOUNT



TCS:
BUS

For surface-mount

With 1, 2 or 4 bell buttons

4 call destinations without numeric keypad

999 call destinations with numeric keypad

Colour camera with a detection angle of 80°

Night lighting



IP VIDEO FRONT DOOR STATION	Item no.
1 button, white illumination	AVD94010-0010
2 buttons, white illumination	AVD94020-0010
4 buttons, white illumination	AVD95040-0010

IP VIDEO FRONT DOOR STATION WITH NUMERIC KEYPAD	Item no.
1 button, white illumination	AVD97010-0010
4 buttons, white illumination	AVD98040-0010

ACCESSORY	HxWxD in mm	Item no.
Weather protection roof, aluminium	83 x 140 x 60	PRODA-EN
Mounting plate, aluminium anodised natural		Mounting plate

VARIANTS

1 button



2 buttons



3 buttons



For up to
999 call
destinations
with numeric
keypad

SERIES AVD IP

PRODUCT FEATURES

- > IP video front door station for surface-mount
- > Number of bell buttons: 1, 2 or 4
- > Type of mounting: surface-mount
- > Type of housing: surface-mounted housing
- > Audio: G.711u / G.711a / G.726-32b / GSM / G722 / G729
- > Material of the housing: aluminium
- > Colour of the housing: anodised natural
- > Material of the bell buttons: metal with maintenance-free contacts
- > Shatter-proof name plate glass
- > Name plates illuminates with energy-saving LEDs
- > Opening principle: concealed screws

CAMERA FEATURES

- > Colour camera
- > Daytime/nighttime operation: automatically
- > Video: series JPEG, MJPG / stream H.263, H.264
- > Detection angle: 80°
- > Maximum resolution: 640 x 480 pixel

EXTENDED FEATURES

- > Number of call destinations: 999 with numeric keypad
- > Calling two parallel call destinations: possible
- > Group call functionality: adjustable
- > Echo suppression: full duplex
- > Sending images: via mail
- > VoIP protocol: SIP 2.0 / RFC3261
- > SIP connection: via P2P or PBX
- > Compatibility: all SIP (image) phones / Softphones
- > Name plates: white backlit
- > Configuration: via web interface
- > Error indication: red LED

TECHNICAL DATA

- > Technology: network technology
- > Power supply: via Power over Ethernet (PoE) / 12 V
- > Number of potential-free relay contacts: 2
- > Camera field H x W mm: 38x82
- > Name plate H x W mm: 72x74
- > Acceptable ambient temperature: -20 to +60 °C
- > UV-resistance: unlimited

SCOPE OF DELIVERY

- > For labelling: name plates

<http://www.tcsag.de/produkte>

ACCESSORY



Information
field module

Weather
protection roof


Mounting plate
(upon request)

Information field module, weather protection roof or mounting plate easy to mount


The backlit information field module can be flush-mounted or can also be placed on plaster in the format 90 x 135 x 20 mm. The weather protection roof is attached to the front door station as an accessory using adhesive. The mounting plate for surface-mount of the front door stations on uneven ground is available in individual length upon request.

DIMENSIONS (IN MM)

Front door
station



Front door station with code lock



CONTACT US

In case of any questions on planning,
please contact our technical hotline

Phone +49 4194 9881-188
(German landline)

Send your inquiry to

Fax +49 4194 9881-189
Email hotline@tcsag.de