

SERIES PAK

FRONT DOOR STATION AUDIO

SURFACE-MOUNT

TCS:
BUS



For up to 8 flats

Minimum product depth of only 16 mm

Can be opened without screws via win:clip™

Name plates made of shatter-proof acrylic glass

Name plates illuminated with energy-saving LEDs

Timeless design in robust aluminium

In anodised natural

RAL colours and special anodised colours
on request



FRONT DOOR STATION	HxWxD in mm	Item no.
1 button	153 x 104 x 16	PAK01-EN
2 buttons	153 x 104 x 16	PAK02-EN
3 buttons	153 x 104 x 16	PAK03-EN
4 buttons	153 x 104 x 16	PAK04-EN
5 buttons	175 x 104 x 16	PAK05-EN
6 buttons	197 x 104 x 16	PAK06-EN
7 buttons	219 x 104 x 16	PAK07-EN
8 buttons	241 x 104 x 16	PAK08-EN


ACCESSORY	HxWxD in mm	Item no.
Mounting plate for ...		
PAK01-EN	247 x 170 x 3	ZAM1101-0010
PAK02/03-EN	284 x 170 x 3	ZAM1102-0010
PAK04/05/06-EN	338 x 170 x 3	ZAM1103-0010
PAK07/08-EN	413 x 170 x 3	ZAM1104-0010
Weather protection roof	61 x 109 x 50	PAKDA-EN
win:clip key (10 pcs.)		E03458

VARIANTS

1 to 4 buttons



5 to 8 buttons



SERIES PAK

PRODUCT FEATURES

- > Audio front door station
- > Number of bell buttons: up to 8
- > Type of mounting: surface-mount
- > Type of housing: surface-mounted housing
- > Voice transmission: via integrated loudspeaker
- > Material of the housing: aluminium
- > Colour of the housing: anodised natural
- > Material of the bell buttons: metal with maintenance-free contacts
- > Shatter-proof name plate glass
- > Name plate illumination with energy-saving LEDs
- > Opening principle: win:clip
- > Volume voice transmission: adjustable
- > Volume microphone sensitivity: adjustable

EXTENDED FEATURES

- > Light switch function: at unprogrammed bell button
- > Name plates: white backlit
- > Mixed installation of audio, video, access control: possible
- > Commissioning and configuration: manually, with Service Device, with configuration software
- > Memory of system configuration: pluggable

TECHNICAL DATA

- > Technology: TCS:BUS
- > Number of wires: 3 necessary
- > Input current in resting position: 11 mA
- > Maximum input current: 21 mA
- > Acceptable ambient temperature: -20 to +50 °C
- > UV-resistance: unlimited

SCOPE OF DELIVERY


- > for labelling: name plates
- > for exchanging name plates: win:clip key

ACCESSORY

- > Mounting plate, anodised natural: ZAM1101-0010
- > Weather protection roof series PAK, anodised natural: PAKDA-EN

<https://www.tcsag.de/en/products/>

DIMENSIONS (IN MM)



ACCESSORY



Mounting plates

Mounting plates made of anodised aluminium natural are used for a clean surface-mount on uneven grounds.



Weather protection roof

The weather protection roof is simply mounted with adhesive for protection against climatic influences.

CONTACT US

In case of any questions on planning, please contact our technical hotline

Phone +49 4194 9881-188
(German landline)

Send your inquiry to

Fax +49 4194 9881-189
Email hotline@tcsag.de