Datasheet

02-2011

Staircase light control unit

Functionality controlling, switching, storaging		
number of selectable functions		max. 10
3 resp. 4 conductor circuits		automatic detection
long-term function	min	60
light switch time	min	0.5 to 20 (continously adjustable)
warning before switch-off (DIN 18015-2)		LED (2x double blink)
time period switch-off warning		adjustable
downstream immediately		yes
Electrical features		
zero-crossing contactor		yes
nominal voltage	V / Hz	230 / 50-60
additional control input	V AC/DC	8 to 240
switching capacity		230 V | 50/60 Hz | cos Phi=1 : max. 16 A
glow lamp voltage	mA	max. 150
Mechanical features		
mounting		DIN-rail mounting
type of housing		DIN-rail housing
material of the housing		plastic
weight	g	100
Dimensions H x W x (D)		
DIN-rail housing	mm	95 x 25 x 70
separating units	SU	1
Climatic features		
acceptable ambient temperature	°C	0 to +40
degree of protection	IP	20
Scope of delivery		
staircase light control unit		FNA1000-0400 (incl. product information)

Staircase light control unit as multi function device with 10 functions.

FNA1000-0400

For questions regarding planning, please contact our technical support

Send your enquiry per Mail to:
hotline@tcsag.de

TCS TürControlSysteme AG PF1251 · D-39302 Genthin · Mail info@tcsag.de · **www.tcsag.de**
TCS Österreich GmbH Gewerbepark 21 · A-2821 Lanzenkirchen ·Tel: + 43(0)2627-45 266 0 · Fax + 43 (0)2627-4526620 · Mail office@tcs-austria.at

Subject to technical modifications.
Images shown are not binding.