Call relay (flush-mount)

Fields of application		
application		for controlling additional bells and radio bells | evaluating the special key function of the indoor station | for specific door release
Functionality controling, switching, storaging		
door release function		with potential-free relay contact (closing contact 24 V DC / 2 A)
relay switch time	s	2 (adjustable factory setting)
Electrical features		
supply voltage	V	24
input current I(a)	mA	1.2 (2-wire) | 0.4 (3-wire)
input current I(P)	mA	0.8
input current I(Pmax), max.	mA	6.5
Mechanical features		
mounting		built into one gang boxes
material of the housing		plastic
weight	g	25
System features		
signal transmission and power supply		polarity-free and short-circuit protected 2-wire TCS:BUS
wiring technique (number of wires)		2 or 3 possible
number of suitable TRE2 devices in 2-wire technique		max. 10
Commissioning and maintenance		
programming		one-time manually (in delivery state) | with Service Device | with configo™
parameters adjustable with Service Devcie, configo™		relay switch time
Dimensions H x W x (D)		
DIN-rail housing	mm	52 x 52 x 23
connection diameter	mm	0.4 to 0.8
Climatic features		
acceptable ambient temperature	°C	-20 to +50
Scope of delivery		
call relay (flush-mount)		TRE2-EB (incl. product information)

Built-in call relay with own :BUS connection for a location-independent installation.

TRE2-EB

For questions regarding planning, please contact our technical support

Send your enquiry by Mail to:
hotline@tcsag.de

TCS TürControlSysteme AG PF1251 · D-39302 Genthin · Mail info@tcsag.de · **www.tcsag.de**
TCS Österreich GmbH Gewerbepark 21 · A-2821 Lanzenkirchen ·Tel: + 43(0)2627-45 266 0 · Fax + 43 (0)2627-4526620 · Mail office@tcs-austria.at

Subject to technical modifications.
Images shown are not binding.