

CARUS ORIGO

INDOOR STATION VIDEO

SURFACE-MOUNT



TCS:
BUS

Housing milled of aluminium full material

3.5" digital display

On-screen display fo comfortable operation

Central image storage (FVM1000) can be used in comfort mode

Receipt of TCS:BUS messages

Extended comfort functions such as internal calls and switching functions

13 ring tones can be selected

For surface-mount or as tabletop device

Aluminium anodised silver, anodised bronze, anodised champagne or anodised black



VARIANTS

Wall-mount device

Tabletop device



Item no.

Carus ORIGO, wall-mount device

[CAE2000-015..](#)

Carus ORIGO, tabletop device

[CAE2010-015..](#)

Central image storage

[FVM1000-0400](#)

...0 anodised silver, ...1 anodised bronze, ...2 anodised champagne, ...6 anodised black

CARUS ORIGO

PRODUCT FEATURES

- > Video indoor station for hands-free talking
- > Type of mounting: surface-mount
- > Type of housing: surface-mounted housing
- > Material of the housing: aluminium, refined by hand
- > Colour of the housing: anodised silver
- > Number of acoustic call distinctions: 4 (up to 2 from front door stations)
- > Voice transmission: hands-free talking/duplex communication (can be activated)
- > Number of ring tones: 13
- > Automatic hands-free talking after internal call: can be activated
- > Audio privacy function: yes
- > Automatic call cut-OFF: yes
- > Call acceptance: at speech button
- > Ring tone mute: at call-OFF button
- > Ring tone volume: adjustable

IMAGE/VIDEO FEATURES

- > Type of display: digital TFT, colour
- > Size of display: 3.5"
- > Resolution : 320x240 pixel
- > Video privacy function: yes
- > Image activation/camera selection: at image button
- > Colour saturation/brightness/contrast: adjustable
- > Comfort mode: new images are stored in the central image storage

EXTENDED FEATURES

- > Door release function: at door release button
- > Door release automatic: can be activated
- > Light switch function: at function button
- > Control function: can be activated
- > Parallel call: can be activated
- > Internal call: can be activated

- > Door release automatic: can be activated
- > Call diversion: can be activated
- > Floor door release function: can be activated
- > Floor call: possible (1)
- > LED (red): ring tone mute
- > LED (green): door and internal calls (short-term memory), busy indication, indication for image recording
- > OSD menu: yes
- > Menu control: at menu and navigation buttons
- > Operation indication: OSD menu
- > Error indication: optical/acoustic (total error indication at both LEDs)
- > Receipt of TCS:BUS messages: possible
- > Mixed installation audio, video, access control: possible
- > Commissioning and configuration: manually, with Service Device, with configuration software

TECHNICAL DATA


- > Technology: TCS:BUS
- > Number of wires: 6 necessary
- > Input current in resting position: 16.5 mA
- > Maximum input current: 175 mA
- > Recommended mounting height: 1.6 m
- > Acceptable ambient temperature: 0 to +40 °C

ACCESSORY

- > Central image storage: FVM1000-0400

<http://www.tcsag.de/produkte>

DIMENSIONS (IN MM)



CONTACT

In case of any questions on planning, please contact our technical hotline

Phone +49 4194 9881-188
(German landline)

Send your inquiry to

Fax +49 4194 9881-189
EMail hotline@tcsag.de