

SKYLINE:TEN BASIC

INDOOR STATION VIDEO

FLUSH-MOUNT



TCS: BUS





USER INTERFACE



Expected comfort already usable at the front door. Via the TCS:BUS the indoor station receives centrally sent text messages. This could be information on the landlord or the manufacterer. Thanks to pre-installed Apps, the indoor station displays calender, current weather forecasts or even the lastest E-Mails. Via browser even surfing the internet is possible.

Touch display with 25.6 cm (10.1") screen

Resolution 1.280 x 800 pixel

Intuitive operation

4 function buttons

Integrated SD card reader to transmit image and music files

Receipt of TCS:BUS messages

Digital image frame with background music

Integrated LAN and WLAN

Aluminium anodised silver or black

	Item no.
skyline:ten BASIC, anodised silver	IVW9010-0261
skyline:ten BASIC, anodised black	IVW9010-0262

SKYLINE:TEN BASIC

PRODUCT FEATURES

- > Video indoor station for hands-free talking
- > Type of mounting: surface-mount with mounting box/ flush-mount with flush-mount box
- > Material of the housing: aluminium
- > Colour of the housing: anodised silver
- > Number of acoustic call distinctions: 4 (up to 2 from front door stations)
- Voice transmission: hands-free talking/duplex communication (can be activated)
- > Number of ring tones: 13
- > Import of individual ring tones: possible
- > Automatic hands-free talking after internal call: can be activated
- > Audio privacy function: yes
- > Automatic call cut-OFF: yes
- > Call acceptance: at speech button
- > Ring tone mute: via OSD menu
- > Ring tone volume: adjustable
- > Volume microphone and loudspeaker: adjustable
- > Network: LAN and WLAN
- > Digital image frame: yes
- > Voices: German/English
- Functions in the OSD menu: (de)activation of the touch function, programming, load to factory settings

IMAGE/VIDEO FEATURES

- > Display: 25.6 cm (10.1") colour
- > Display type: touch screen 1280 x 800 pixel
- > Video privacy function: yes
- > Camera selection: via OSD menu
- > Camera control: via OSD menu
- > Color saturation/brightness/contrast: adjustable
- > Automatic image storing in case of a door call: yes

- > Additional connections: floor push-button
- > Floor door release function: can be activated
- > Floor call: 1 possible
- > LED (red): ring tone mute
- > LED (green): door and internal calls (short-term memory), busy indication, indication for image recording
- > OSD menu: yes
- > Menu control: at menu and navigation buttons
- > Operation indication: OSD menu
- Error indication: optical/acoustic (total error indication at both LEDs)
- > Receipt of TCS:BUS messages: possible
- > User Apps: E-Mail, calender and internet browser
- > Mixed installation audio, video, access control: possible
- Commissioning and configuration: manually, with Service Device, with configuration software
- > Designation of front door stations, cameras, control functions: configurable via OSD menu

TECHNICAL DATA


- > Technology: TCS:BUS
- > Number of wires: 6 necessary
- > Input current in resting position: 60 mA
- > Maximum input current: 330 mA
- > Recommended mounting height: 1.6 m
- > Acceptable ambient temperature: 0 to +40 °C
- > Degree of protection: IP30

http://www.tcsag.de/produkte

EXTENDED FEATURES

- > Home automation: central ON/central OFF
- > Door release function: via OSD menu
- > Door release automatic: via OSD menu
- > Light switch function: via OSD menu
- > Control function: maximum 20 via OSD menu
- > Parallel call, internal call: configurable
- > Door release automatic: via OSD menu
- > Call diversion: configurable
- Additional functions for calling and switching: maximum 10 internal calls / maximum 10 control functions

DIMENSIONS (IN MM)



CONTACT

In case of any questions on planning, please contact our technical hotline

Phone +49 4194 9881-188 (German landline)

Send your inquiry to

Fax +49 4194 9881-189 EMail hotline@tcsag.de 42 (Width = 227)