

# VIDEO DOOR PHONE

INDOOR STATION VIDEO

SURFACE-MOUNT



TCS: BUS

8.9 cm (3.5") digital display

Simple basic functionality

For discret talking with handset

Ring tone mute

Intuitive operation

With function button

Optional as desktop accessory

Plastics white



#### **ACCESSORY**



Desktop accessory

	Item no.
Video door phone	IVH3222-0140
Desktop accessory	ZIT3222-0030

## VIDEO DOOR PHONE

#### PRODUCT FEATURES

- > Video indoor station
- > Type of mounting: surface-mount (on flush-mount socket)
- > Type of housing: surface-mounted housing
- > Material of the housing: plastics (matted)
- > Colour of the housing: white
- > Lower cover: can be pre-installed with plugged screw terminal
- > Number of acoustic call distinctions: 4 (up to 2 from front door stations)
- > Voice tranmission: with handset
- > Number of ring tones: 7
- > Audio privacy function: yes
- > Automatic call cut-OFF: yes
- > Ring tone mute: at call-OFF switch
- > Ring tone volume: adjustable

#### IMAGE/VIDEO FEATURES

- > Type of display: digital colour TFT
- > Size of display: 8.9 cm (3.5")
- > Resolution: 320x240 pixel
- > Video privacy function: yes
- > Image activation: at function button
- > Brightness/contrast: adjustable

#### **EXTENDED FEATURES**


- > Door release function: at door release button
- > Light switch function: can be activated
- > Control function: can be activated
- > Parallel call: can be activated
- > Mixed installation audio, video, access control: possible
- > Commissioning and configuration: manaully, with Service Device, with configuration software

#### TECHNICAL DATA

- > Technology: TCS:BUS
- > Number of wires: 6 neccessary
- > Input current in resting position I(P): 4 mA
- > Maximum input current I(Pmax)l: 90 mA
- > Surface-mounted housing HxWxDmm: 250 x100 x 50 / 28 (with/without handset)
- > Recommended mounting height: 1.6 m
- > Acceptable ambient temperature: 0 to +40 °C

http://www.tcsag.de/produkte

#### DIMENSIONS (IN MM)



### CONTACT

In case of any questions on planning, please contact our technical hotline

Phone +49 4194 9881-188 (German landline)

Send your inquiry to

Fax +49 4194 9881-189 EMail hotline@tcsag.de