

Built-in door release relay		
Functionality controlling, switching, storing		
door release function		with potential-free relay contact (two-way contact 24 V DC / 2 A)
door release time	s	3 (adjustable factory setting)
Electrical features		
input current I(a)	mA	0.4
input current I(P), stand-by	mA	0.8
input current I(Pmax), max.	V	16
Mechanical features		
type of installation		for DIN-rail (DIN EN 50022) location independent installation with an own BUS connection
type of housing		DIN-rail housing (1 SU)
System features		
signal transmission and power supply		polarity-free and short-circuit protected 2-wire TCS:BUS
wiring technique (number of wires)		3 necessary
Commissioning and maintenance		
status indication		LED (yellow)
programming		with Service Device configo™
evaluation control functions		possible
Dimensions H x W x D		
DIN-rail housing	mm	85 x 17.5 x 60
max. line diameter	mm	0.8
Climatic characteristics		
acceptable ambient temperature	°C	-5 to +40
degree of protection	IP	20
Scope of delivery		
built-in door release relay for front-door stations		FAA1200-0400 (incl. product information)

Built-in door release relay for specific door release when more than one front-door station is integrated into a system.

FAA1200-0400



For questions regarding planning, please contact our technical support

Send your enquiry per Mail to:
hotline@tcsag.de