

Video distributor, double, flush-mount

Fields of application

application		reception of a video signal and distribution to two active outputs, which are independent from one another
-------------	--	--

Functionality

number of video inputs		1
number of video outputs		2 (active, independent from one another)
amplification brightness		adjustable factory setting: amplification 1
voltage amplification		independent from the output load
loop throughs		up to 25 video signal distributors can be looped through
minimum amplification	dB	0 (1 Vpp)
maximum amplification	dB	12 (4 Vpp)

Electrical features

supply voltage	V	24
input current I(a), standby	mA	0,0
input current I(P), standby	mA	40
input current I(Pmax) max.	mA	60
input impedance (J1 plugged)	Ohm	100
setting the amplification	dB	0 to 12
max. output level		4 Vpp at 100 Ohm (with 1 Vpp at the entrance)

Mechanical features

type of installation		DIN-rail mounting
type of housing		DIN-rail housing
material of the housing		plastics
weight	g	30

Dimension H x W x D

DIN-rail housing	mm	52 x 52 x 23
------------------	----	--------------

Climatic characteristics

acceptable ambient temperature	°C	-20 to +50
--------------------------------	----	------------

Scope of delivery

video distributor, double, flush-mount		FVY1200-0600 (incl. product information)
--	--	--

Video distributor to supply up to two strands with video signals.

FVY1200-0600



For questions regarding planning, please contact our technical support

Send your enquiry to:
hotline@tcsag.de