

Cylinder camera		
Fields of application		
application		indoors   outdoors
Camera features		
detecting angle		110° (wide angle)   80° (standard)   45° (tele)   25° (super tele)
type of camera		color
image sensor	cm (")	0.8 (1/3) SONY CCD
resolution	TVL	500
photo sensitivity	Lux	0.25 at F 1.4
lens		wide angle (FVK3210-0)   standard (FVK3220-0)   tele (FVK3230-0)   super tele (FVK3240-0)
focal length f	mm	2.9 (wide angle)   4.3 (standard)   8.0 (tele)   16.0 (super tele)
Mechanical features		
pan and tilt range		360° pan   90° tilt (mechanically adjustable)
mounting		wall mounting   ceiling mounting
material of the housing		aluminium
color		beige painted
weight	g	234
Electrical features		
input current I(a)	mA	0.0
input current I(P), standby	mA	100
input current I(Pmax)	mA	100
System features		
signal transmission and power supply		polarity-free and short-circuit protected 2-wire TCS:BUS
wiring technique (number of wires)		6
Dimensions H x W (x D)		
camera	mm	Ø 21 x 77   Ø 30 x 85 (with protecting roof)
two-wire video transmitter	mm	52 x 52 x 23
Climatic features		
acceptable ambient temperature	°C	-20 to +50
degree of protection		IP 68
UV resistance		unlimited
Scope of delivery		
cylinder camera		FVK32x0-0 (incl. 2.6 m cable)
for mounting		mounting base
sun protection		protecting roof
for connection		two-wire video transmitter FVW2000-0600

Cylinder camera for ceiling mounting

**FVK32x0-0**



Cylinder camera for wall mounting

**FVK32x0-0**



For questions regarding planning, please contact our technical support

Send your enquiry by Mail to:  
**hotline@tcsag.de**